

Manufacturing and trading company «Ecopolymer»

109029, Moscow, st. Srednyaya Kalitnikovskaya, 28, bldg 2, fl 2 , rm 1, rm 10 Tel.: +7 (495) 710-86-22. E-mail: tpp@ecopolymer.com www.ecopolymer.com

QUESTIONNAIRE

FOR STOPLOG SELECTION

Company Legal name				
Address				
	Position			
Tel	Fax			
1. Required quantity	pcs.			
2. Operating medium:				
☐ Wastewater	Natural water			
Other				
3. Material:				
AISI 304	☐ AISI 321	AISI 316L		
Othere	_	 .		
4. Stoplog installation type	:			
Trench casing	Anchoring inside the channel	I .		
5. Channel/wall material, to which the stoplog is to be assembled:				
Mass concrete	Precast concrete	☐ Steel		
6. Sealing direction:				
Unidirectional	☐ Bidirectional			

7. Chamier (opening) unitensions in s	topios	instantation place:		
H	8	ht ht		
Channel width (W)	mm	Opening width (W)		mm
Channel height (H)	mm	Opening height (H)		mm
Wall thickness (a)				mm
()		Distance to overlap (h2) Distance to bottom (h1)		mm
8. Additional information:				
Responsible person Full name		(Signati	ure)